

Package ‘shinyglass’

August 2, 2026

Type Package

Title Liquid Glass Design Themes for 'shiny' Applications

Version 0.1.1

Description Drop-in Liquid Glass themes for 'shiny'. Call `glass_theme()` and pass the result to `fluidPage()`, `navbarPage()`, or any 'bslib'-aware page function to get translucent surfaces, backdrop blur, and system typography on 'Bootstrap' components. Light and dark presets are included, with options for accent color, blur, and corner radius.

License GPL-3

URL <https://ericrayanderson.github.io/shinyglass/>,
<https://github.com/ericrayanderson/shinyglass>

BugReports <https://github.com/ericrayanderson/shinyglass/issues>

Encoding UTF-8

Imports bslib (>= 0.5.0), htmltools (>= 0.5.0), sass (>= 0.4.0)

Suggests DT, ggplot2, shiny (>= 1.5.0), testthat (>= 3.0.0)

Config/testthat/edition 3

Config/roxygen2/markdown TRUE

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Eric Anderson [aut, cre]

Maintainer Eric Anderson <eric.ray.anderson@gmail.com>

Repository CRAN

Date/Publication 2026-08-02 21:30:02 UTC

Contents

glass_theme	2
Index	4

glass_theme

*Liquid Glass theme for Shiny***Description**

Create a `bslib::bs_theme()` styled with a Liquid Glass look: translucent surfaces, backdrop blur, soft depth, and system typography. Pass the result to `theme =` on `fluidPage()`, `navbarPage()`, `bslib::page_sidebar()`, or any other page function that accepts a bslib theme.

Usage

```
glass_theme(
  preset = c("light", "dark"),
  primary = "#007AFF",
  blur = 28,
  saturation = 200,
  radius = "1.25rem",
  ...
)
```

Arguments

<code>preset</code>	"light" or "dark". Switches the full color system.
<code>primary</code>	Accent color for buttons, links, and focus rings. Defaults to system blue (#007AFF).
<code>blur</code>	Backdrop blur radius in pixels.
<code>saturation</code>	Backdrop saturation percentage.
<code>radius</code>	Default border radius for glass surfaces (CSS length).
<code>...</code>	Additional arguments forwarded to <code>bslib::bs_theme()</code> .

Value

A `bslib::bs_theme()` object suitable for Shiny page functions.

Examples

```
theme <- glass_theme()
dark <- glass_theme(preset = "dark", primary = "#BF5AF2")

if (interactive()) {
  library(shiny)

  ui <- fluidPage(
    theme = glass_theme(),
    titlePanel("Liquid Glass"),
    selectInput("color", "Color", c("Blue", "Purple", "Orange")),
    plotOutput("plot")
  )
}
```

```
  shinyApp(ui, function(...) {})  
}
```

Index

`bslib::bs_theme()`, [2](#)

`glass_theme`, [2](#)